




## Radlader Coupler to Wheel loader



All are CE-marked! Weight  
- approximately!



To meet the demands of the EC Machinery Directive 98/37/EEC, the directions EN 291-1, EN 292-2, EN 474-1 and EN 474-5 is all hydraulic quick-couplers standard equipped with electric 2 ways electrovalves 24 Volt (12 Volt) and 1 pair of Tema 3/4" male for hydraulic function (the letter C after art.no. confirms this). The machine needs 3:rd hydraulic circuit and el-cable/switch.

Above can only be renounced when the machine has a sepearate hydraulic locking system for the quick-coupler and on the quick-coupler the extra hydraulic male 3/4", as above mentioned, is not available (there is no letter C after the art.no.).

The price will be reduced

| Article no | Machine weight | Coupler type | Specification |
|------------|----------------|--------------|---------------|
| 4110...    | 1-5 ton        | ABL 60       | Standard      |
| 4120...    | 5-10 ton       | ABL 60       | Standard      |

|            |           |         |                     |
|------------|-----------|---------|---------------------|
| 4121...    | 5-10 ton  | ABL 60  | Inklusive länkmarm  |
| 4420,30... | 5-10 ton  | ABL 120 | Inklusive länkmarm  |
| 4430...    | 1-10 ton  | ABL 120 | Teleskopplastare    |
| 4440...    | 10-14 ton | ABL 120 | Standard            |
| 4450...    | 10-14 ton | ABL 120 | Standard 3-punkt    |
| 4460...    | 14-20 ton | ABL 120 | Standard            |
| 4470...    | 20-25 ton | ABL 120 | Standard            |
| 4670...    | 19-26 ton | ABL 180 | Standard            |
| 4680..     | 26-35 ton | ABL 180 | Standard            |
| 5560...    | 20-29 ton | ABL 300 | Kewaco K-300 rak    |
| 5570...    | 25-45 ton | ABL 325 | Modell svängd       |
| 5590...    | 30-45 ton | ABL 300 | Kewaco K-300 rak    |
| 5780...    | 40-60 ton | ABL 525 | Kewaco K-525 knäckt |
| 5790...    | 40-60 ton | ABL 500 | Kewaco K-500 rak    |
| 5791...    | 60-90 ton | ABL 500 | Kewaco K-500 rak    |

Other dimensions on request: +46 [0] 382 676 00 [info@abl.se](mailto:info@abl.se)

ABL Box 200 576 24 SÄVSJÖ SWEDEN Tel +46 (0) 382 676 00 Fax +46 (0) 382 615 20 [info@abl.se](mailto:info@abl.se) [www.abl.se](http://www.abl.se)

