



Radlader High dump medium bucket



All are CE-marked! Weight
- approximately!



The bucket is clean inside. Allowed load 1,4 ton/m³.

Meant for wood chips, seeds, coal etc. The cylinders has built-in suspension in both ends and adjustable flow-valve. Bolt-On is standard. Exclusive hydraulic hoses to machine.

Extra equipment: Direct installation

The choice of Bolt-On decides the number of edges and also the dimension of the same. [Bolt-On types: Volvo type I, II, III and CAT-system]

Article no	Volume [lit]	Width [mm]	Depth [mm]	Height [mm]	Weight [kg]	Base Edge
6510013220	1300	2200/1800	1080	1000	1360	200x20
6510016220	1600	2200/1800	1080	1070	1420	200x20
6510018220	1800	2200/1800	1080	1125	1590	200x20
6510021240	2100	2400/2000	1080	1125	1660	200x25
6510025250	2500	2500/2100	1190	1175	1760	200x25
6510030250	3000	2500/2100	1250	1250	1875	250x25
6510030270	3000	2700/2300	1200	1200	1980	250x25

6510035250	3500	2500/2100	1330	1300	2060	250x25
6510038270	3800	2700/2310	1330	1300	2120	250x25
6510040250	4000	2500/2100	1450	1540	2190	250x25
6510040270	4000	2700/2300	1380	1540	2300	250x25
6510050270	5000	2700/2300	1490	1660	2500	250x25
6510060270	6000	2700/2300	1670	1840	2890	250x25
6510060280	6000	2800/2400	1620	1840	3000	250x30
6510060300	6000	3000/2600	1560	1800	3130	250x30
6510070270	7000	2700/2300	1860	1980	3210	250x30
6510070280	7000	2800/2400	1820	1950	3360	250x30
6510070300	7000	3000/2600	1750	1900	3420	250x30
6510070320	7000	3200/2800	1700	1830	3500	250x30
6510080300	8000	3000/2600	1850	2025	3730	300x30

Other dimensions on request: +46 [0] 382 676 00 info@abl.se

ABL Box 200 576 24 SÄVSJÖ SWEDEN Tel +46 (0) 382 676 00 Fax +46 (0) 382 615 20 info@abl.se www.abl.se

